

# Mira Element

## Mixer Shower Range



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

Its simple, uncluttered look is ideal for a contemporary or family bathroom, plus its single control makes it easy to use.

### Product Information

Description	Colour	Product No.
Mira Element EV	Chrome	1.1656.001
Mira Element BIV	Chrome	1.1656.002
Mira Element BIR	Chrome	1.1656.003

### Features & Benefits

#### Temperature control

Thermostatic temperature stability

#### Easy to fit

Quickly and easily fits onto reversed inlet supplies

Adjustable slide bar fits over holes left by previous shower kit (400mm-600mm)

#### Easy to service

Large, long-life filters and replaceable cartridge

#### For your customer

One control for on/off and temperature

Mira Magni-flo™ technology delivers up to 3x more flow, even at low pressure

4 spray 9cm showerhead with rub-clean nozzles



MIRA ELEMENT EV



MIRA ELEMENT BIR

MIRA ELEMENT BIV

# Product Specification

## Tech Details

### Temperature control

Control type: Thermostatic

### Installation

Water entry points: Rising, falling or rear

Inlet connections: 15 mm compression (EV, BIV & BIR)

Outlet connections: ½" BSP Male Flat Face (EV) or 15mm compression (BIV & BIR)

Reversed inlets supported: No = hot left, cold right only

### Supply Conditions (hot and cold)

Cold water range: Up to 25°C

Hot water range: 50°C-85°C (operating)  
55°C-65°C (recommended)

Minimum maintained pressure: 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

### Performance

Flow rate (at handset): 13 l/min at 0.5 bar

Temperature stability: ± 2°C

### Safety Features

Automatic shutdown: Shutdown within 2 secs

Factory set to safe max temp: Factory set to 41°C

Adjustable maximum temperature for on-site conditions

### Approvals

WRAS approved (Water Regulations Advisory Scheme)



## Dimensions

