

Tech Details

Temperature contro

Control type: Advanced pressure stabilised

Installation

Power options: 7.5kW 240V AC (6.9kW 230V AC); 9.0kW 240V AC (8.3kW 230V AC); 9.8kW 240v AC (9.0kW 230V AC); 10.8kW 240V AC (9.9kW 230V AC)

Supply voltage: $230v \pm 10\%$

Supply rating: 32 amp (7.5kW); 40 amp (9.0kW); 45 amp (9.8 & 10.8kW)

Terminal Block connections: Maximum 16mm2

Water entry points: Left (rising, falling & rear)

Cable entry points: Left (rising, falling & rear)

Inlet connections: Brass inlet connector. 15mm compression fitting

Outlet connections: 1/2" BSP Male

Supply Conditions

Minimum maintained pressure; 7.5, 9.0 & 9.8 kW: 0.7 bar (7 metre head); 10.8kW: 1.0 bar (10 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Performance

Temperature stability: ± 6°C

Safety Features

Phased shutdown: Yes

Factory set to safe max temp: No

Mira Sensi-flo™: Yes

Accessories

Wide range of accessories available at www.mirashowers.co.uk

Approvals

Energy Efficiency: Class A



Dimensions





