

## Thermostatic Mixing Valve

inspiration,  
**performance**  
and peace of mind,  
**protection**

### Description

Inta's new anti-legionella thermostatic mixing valve comes equipped with a by-pass device to disinfect the valve and the waterway up to the faucet without having to be disassembled while delivering safe, blended hot water to taps, showers, bidets and other water outlets.

Thanks to the valves temperature sensor which dilates and contracts depending on the perceived temperature, it constantly sets the right proportion between hot and cold water automatically regulating the water flow between hot and cold until the perfect temperature has been achieved.



- Operating pressure range of 0.2 to 10 bar
- Thermal cartridge technology
- Temperature stability of +/-2°C
- Fail safe on hot and cold supplies
- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Chrome Plated

### Product Range

Description	Code
Thermostatic Mixing Valve 15mm with Built in Diverter for Sterilisation	60015CP
Thermostatic Mixing Valve 15mm	62015CP



## Thermostatic Mixing Valve

### Technical Specification

Max Inlet Pressure static	10 Bar
Min Inlet Pressure dynamic	0.2 Bar
Max Inlet Temperature	90°C
Factory Pre-set Temperature	38°C with max temp stop
Min Temperature to achieve hot or cold failsafe	10°C
System Installation	Unvented, Pressurised, Gravity and Combination Boilers

