

shower valves - Sulis Thermostatic Bar Shower

Introduction

The Sulis range from Inta will add a touch of elegance to all bathrooms in your home. Gentle curves and sleek lines are the defining features. Behind the looks is the thermostatic reliability on which Inta has built its reputation. With concealed, exposed, over the bath and basin mixer options the Sulis can protect those in a vulnerable position wherever they are installed - beautifully.

total control



sulis thermostatic bar shower
with flexible slide rail kit
80009CP

- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Thermal cartridge technology
- Temperature stability of $\pm 2^{\circ}\text{C}$
- Fail safe protection on both the hot and cold supplies
- Operating pressure range of 0.2 to 5 bar
- WRAS and TMV2 approved

Product Range

Description	Code
Sulis thermostatic bar shower with flexible riser kit	80009CP
Sulis thermostatic bar shower	80002CP
Sulis flexible slide rail kit	80007CP



shower valves - Sulis Thermostatic Bar Shower

Features

Technical Specification

Max Inlet Pressure (static)	5 Bar
Min Inlet Pressure (dynamic)	0.2 Bar
Max Inlet Temperature	85°C
Factory Pre-set Temperature	38°C with max temp stop
Inlet Connections	G 3/4" F BSP (valve body)
Outlet Connections	G 1/2" F BSP
Min Temperature differential to achieve hot or cold failsafe	15°C

System Installation: Unvented, Pressurised, Gravity and Combination Boilers

