



#### Product features:

- Metal construction throughout
- Thermostatic valve for safety & comfort
- Minimalist planate design form
- Supplied with adjustable centre inlets
- Luscious European quality chromium plate finish


#### Packaged properties:

Box length (mm): 290      Box depth(mm): 85  
Box width(mm): 95      Boxed weight (Kg): 2.0

Includes pop up waste?: No


Additional comments:

#### Product dimensions:



- Product mounted where: Wall
- Recommended hole size: N/A mm
- Overall Height / projection: 92 mm
- Exit reach: 65 mm
- Exit height: 32 mm
- Base size: 70x70 mm
- Inlet centre distance(s): 150 +/-25 mm
- Min. fitting depth required: 60 mm
- Max. surface depth: N/A mm

#### Product flow characteristics:



- Min / Max water pressure (bar): 0.20\* / 5.00
- Part G max. mixed flow rate at 3 bar (l/m): 33
- Inlet connection type / length: Eccentric / 50 mm
- Inlet (plumbing connection) / outlet size: 1/2" M / 3/4" M
- Product flow characteristics: N/A
- Non return valve(s) supplied or position: yes, in body
- Aerator type: N/A
- Control valve type: Thermostatic ( )
- Includes output diverter?: N/A
- Inlet meshed particle filters included: 0.60 mm
- Shower hose type / length: N/A / N/A

#### Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

#### Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives