BTZ BF C

BLITZ Tap Range Blitz Bath Filler Chrome



Specification				
Product Type:	Bathroom Tap			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Lever			
Connection Inlet:	3/4" BSP			
Connection Outlet:	M24 Male Flow Straightener			
Number of Tap Holes:	2			
Valve/Cartridge Type:	3/4" Ceramic Disc Valve			
Plumbing System Requirements:	Suitable for all plumbing systems, ideally balanced			
Minimum Dynamic Pressure (bar):	0.2 bar			
Maximum Dynamic Pressure (bar):	5.0 bar			
Maximum Hot Water Temperature °C:	65°C			
Maximum Static Pressure (bar):	10 bar			
Flow Type:	Single			

Dimensions (measurements in mm)

No

Features:

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability
- 3/4" valve

Product Certifications:



WRAS Certificate No: 2006905 WRAS Expiry Date: 30/06/2025

For more products, visit our website:



220 0 150 85 230 **50**► 130

Flow Rates (I/min)								
System Pressure (bar)	0.2	0.5	1	2	3	5		
BTZ BF C (mixed)	14.3	22.6	31.8	44.9	55	71.1		

TECHNICAL



Isolation Included:

