CADET Tap Range Cadet Bath Shower Mixer Chrome

CAD BSM C



Features:

- Long life and easy to use 1/4 turn ceramic disc valves
- Metal back nuts for added durability
- Includes 1.5m hose, rub-clean anti-limescale handset and wall bracket

Product Certifications:



WRAS Certificate No: 1804053 WRAS Expiry Date: 30/04/2023

For more products, visit our website: http://www.bristan.com

TECHNIC/




DATA

S

Specification				
Style:	Contemporary			
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Paddle			
Connection Inlet:	3/4" BSP			
Connection Outlet:	G 1/2"			
Number of Tap Holes:	2			
Valve/Cartridge Type:	3/4" Ceramic Disc Valves			
Plumbing System Requirements:	All			
Working Pressure Range:	Min 0.2 Bar, Max 5.0 Bar			
Maximum Hot Water Temperature: °C	65			
Maximum Dynamic Pressure: (bar)	5			
Maximum Static Pressure: (bar)	10			
Flow Type:	Single Flow			
Flow Rate: (I/min @ 3 bar)	21.3			
Isolation Included:	No			

Dimensions (measurements in mm)



	Flow Rates (I/min)								
	System Pressure (bar)	0.2	0.5	1	2	3	5		
	Through Handset	2.9	5.7	9.5	16	21.3	27.5		
	Bath Filler (Mixed)	20.1	33.7	49.9	69.8	85.4	110.2		
AL 🖌	R DUAL								

APS & SHOWERS

D4

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Telephone: 0844 701 6274. Facsimile: 0844 701 6275. Web Site: www.bristan.com Email: enquire@bristan.com. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.