SDCDUAL07

DAWLISH Shower Range

Dawlish Exposed Thermostatic Dual Control Shower Valve with Premium Fixed Riser Kit and Diverter to Handset Chrome



Specification				
Main Construction Material:	Brass			
No of Controls:	2			
Shower Type:	Mixer			
Shower Head Type:	Fixed and Handset			
Valve/Cartridge Type:	Thermostatic			
Maximum Hot Water Supply Temperature °C:	65			
Maximum Static Pressure: (bar)	10			
Plumbing System Suitability:	Suitable for all plumbing conditions			
Working Pressure Range:	Min: 0.2 Max: 5.0			
Connection Inlet:	1/2"			
Connection Outlet:	1/2"			
Isolation Valve Included:	No			
Check Valve Included:	Yes			

Features:

- Optimised for UK market, designed to work at pressure range of 0.2 - 5.0bar
- Thermostatic temperature control and automatic stop prevent surges of hot or cold water
- Performance Flow to provide a drenching experience
- Adjustable inlet centres, allowing you to use existing pipework with centres measuring anything between 136mm and 158mm
- Large 6" shower rose
- Premium handset

Product Certifications:



1330

Dimensions (measurements in mm)

Additional Information:

 Matching taps are available for the Dawlish range, search Taps on our website to see the complete collection.

Flow Rates (I/min)							
System Pressure (bar)	0.2	0.5	I	2	3	5	
Through Handset (mixed no Flow regulators)	4.6	9.0	13.4	19.5	25.1	30.9	
Through Handset (mixed with Flow regulators)	-	5.2	6.1	6.6	7.2	8.1	
Through Fixed Head (mixed with no Flow regulators)	5.0	9.0	13.5	19.8	27.3	-	
Through Fixed Head (mixed with Flow regulators)	-	5.6	7.4	7.6	7.7	8.5	

TECHNICAL DATA SHEET YEAR



